

EXHIBIT A



US009986435B2

(12) **United States Patent**
Potkonjak et al.

(10) **Patent No.:** **US 9,986,435 B2**

(45) **Date of Patent:** ***May 29, 2018**

(54) **AUTONOMOUS, NON-INTERACTIVE,
CONTEXT-BASED SERVICES FOR
CELLULAR PHONE**

(71) Applicant: **Empire Technology Development
LLC**, Wilmington, DE (US)

(72) Inventors: **Miodrag Potkonjak**, Los Angeles, CA
(US); **Nathan Beckmann**, Cambridge,
MA (US)

(73) Assignee: **EMPIRE TECHNOLOGY
DEVELOPMENT LLC**, Wilmington,
DE (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days. days.

This patent is subject to a terminal dis-
claimer.

(21) Appl. No.: **14/885,515**

(22) Filed: **Oct. 16, 2015**

(65) **Prior Publication Data**

US 2016/0044512 A1 Feb. 11, 2016

Related U.S. Application Data

(63) Continuation of application No. 14/293,376, filed on
Jun. 2, 2014, now Pat. No. 9,177,311, which is a
(Continued)

(51) **Int. Cl.**

H04M 1/66 (2006.01)
H04W 12/06 (2009.01)
H04W 8/22 (2009.01)
H04L 29/08 (2006.01)
H04W 4/16 (2009.01)
G06Q 20/32 (2012.01)

(Continued)

(52) **U.S. Cl.**

CPC **H04W 12/06** (2013.01); **G06Q 20/3224**
(2013.01); **H04L 67/16** (2013.01); **H04M**
1/72569 (2013.01); **H04W 4/025** (2013.01);
H04W 4/14 (2013.01); **H04W 4/16** (2013.01);
H04W 8/22 (2013.01); **H04M 1/663** (2013.01);
H04M 1/72552 (2013.01); **H04W 88/182**
(2013.01)

(58) **Field of Classification Search**

CPC H04W 88/184; H04W 4/12; H04W 4/14;
H04W 12/06; H04W 12/08; H04W 12/12
USPC 455/419, 425, 466, 404.2, 556.1, 456,
455/411; 701/2, 3

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2003/0138092 A1 7/2003 Maekiniemi et al.
2004/0092250 A1 5/2004 Valloppillil
(Continued)

OTHER PUBLICATIONS

Lucy A. Suchman, "Plans and Situated Actions: The Problem of
Human-Machine Communication," Xerox Parc. ISL-6. Feb. 1985,
162pgs.


(Continued)

Primary Examiner — Temica M Beamer

(57) **ABSTRACT**

Examples include autonomously authenticating a financial
transaction, on behalf of the user, without interacting with
the user, via wireless communication link. In various
embodiments, the user's cellular phone may be configured
to process a message that provides at least partial service
context and autonomously authenticate the financial trans-
action.

29 Claims, 5 Drawing Sheets



US 9,986,435 B2

Page 2

Related U.S. Application Data

continuation of application No. 13/941,853, filed on Jul. 15, 2013, now Pat. No. 8,744,429, which is a continuation of application No. 12/415,027, filed on Mar. 31, 2009, now Pat. No. 8,532,642.

2008/0305814 A1 12/2008 Deng et al.
 2010/0121767 A1* 5/2010 Coulter G06Q 20/02
 705/67
 2016/0323709 A1* 11/2016 Dankar H04W 8/00

OTHER PUBLICATIONS**(51) Int. Cl.**

H04W 4/02 (2018.01)
H04W 4/14 (2009.01)
H04M 1/663 (2006.01)
H04M 1/725 (2006.01)
H04W 88/18 (2009.01)

(56)**References Cited****U.S. PATENT DOCUMENTS**

2004/0254868 A1* 12/2004 Kirkland H04W 4/023
 705/35
 2005/0047562 A1 3/2005 Holz et al.
 2006/0079215 A1 4/2006 Perrella et al.
 2006/0135138 A1 6/2006 Lazaridis
 2006/0205393 A1 9/2006 Veen
 2007/0032224 A1 2/2007 Boyer et al.
 2008/0198018 A1 8/2008 Hartley
 2008/0292074 A1 11/2008 Boni et al.

Shoham, Y., "Agent-Oriented Programming," Journal of Artificial Intelligence, 1994.

Yoav Shoham, "An Overview of Agent-Oriented Programming" Software Agents, Chapter 13, pp. 271-290. AAAI Press, Apr. 18, 1997.

Kenneth P. Fishkin, "A taxonomy for and analysis of tangible interfaces" Pers Ubiquit Comput (2004) 8: 347-358.

Helen Cole and Danae Stanton, "Designing mobile technologies to support co-present collaboration" Pers Ubiquit Comput (2003) 7: 365-371.

Antti Oulasvirta and Antti Salovaara, "A Cognitive Meta-Analysis of Design Approaches to Interruptions in Intelligent Environments" pp. 1155-1158, CHI 2004, Late Breaking Results Paper.

Genevieve Bell and Paul Dourish, "Yesterday's tomorrows: notes on ubiquitous computing's dominant vision" Pers Ubiquit Comput (2006).

Mark Weiser, "Creating the Invisible Interface (Invited Talk)" Abstract, UIST Nov. 2-4, 1994.

Antti Oulasvirta and Lauri Sumari, "Mobile Kits and Laptop Trays: Managing Multiple Devices in Mobile Information Work" CHI 2007, Apr. 28-May 3, 2007.

* cited by examiner




FIGURE 1




FIGURE 2




FIGURE 3




FIGURE 4

U.S. Patent

May 29, 2018

Sheet 4 of 5

US 9,986,435 B2




FIGURE 5

U.S. Patent

May 29, 2018

Sheet 5 of 5

US 9,986,435 B2




FIGURE 6

US 9,986,435 B2

1

AUTONOMOUS, NON-INTERACTIVE, CONTEXT-BASED SERVICES FOR CELLULAR PHONE

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a continuation application under 35 U.S.C. § 120 of U.S. application Ser. No. 14/293,376, filed on Jun. 2, 2014, now U.S. Pat. No. 9,177,311, which is a continuation application under 35 U.S.C. § 120 of U.S. application Ser. No. 13/941,853, filed on Jul. 15, 2013, now U.S. Pat. No. 8,744,429, which is a continuation application under 35 U.S.C. § 120 of U.S. application Ser. No. 12/415,027, filed on Mar. 31, 2009, now U.S. Pat. No. 8,532,642, the entire disclosures of which are incorporated herein by reference.

TECHNICAL FIELD

Embodiments of the present disclosure relate to cellular phones, and more particularly, to autonomous, non-interactive context-based services (beyond traditional telephony and personal information management applications) on a cellular phone.

BACKGROUND

Cellular phones have achieved amazing market penetration worldwide, and have become commonplace in modern life. This trend has pushed manufacturers to increase the capabilities of these devices. In their current form, services provided by the cellular phone generally require explicit interaction with the user.

BRIEF DESCRIPTION OF THE DRAWINGS

Embodiments of the present disclosure will be readily understood by the following detailed description in conjunction with the accompanying drawings and the appended claims. To facilitate this description, like reference numerals designate like structural elements. Embodiments of the disclosure are illustrated by way of example and not by way of limitation in the figures of the accompanying drawings.

FIG. 1 illustrates an overview of a cellular phone with autonomous service, in accordance with various embodiments.

FIG. 2 is a block diagram of the cellular phone of FIG. 1 in further details, in accordance with various embodiments.

FIG. 3 illustrates various examples of autonomous servicing of a call, in accordance with various embodiments.

FIG. 4 illustrates various examples of autonomous servicing of messages, in accordance with various embodiments.

FIG. 5 is a flowchart illustrating a method of autonomous service on a cellular phone, in accordance with various embodiments.

FIG. 6 is a block diagram of a computer program product with instructions for providing autonomous service on a cellular phone, in accordance with various embodiments.

DETAILED DESCRIPTION

In the following detailed description, reference is made to the accompanying drawings which form a part hereof wherein like numerals designate like parts throughout, and in which is shown by way of illustration embodiments in

2

which the disclosure may be practiced. It is to be understood that other embodiments may be utilized and structural or logical changes may be made without departing from the scope of the present disclosure. Therefore, the following detailed description is not to be taken in a limiting sense, and the scope of embodiments in accordance with the present disclosure is defined by the appended claims and their equivalents.

Various operations may be described as multiple discrete operations in turn, in a manner that may be helpful in understanding embodiments of the present disclosure; however, the order of description should not be construed to imply that these operations are order dependent. Moreover, some embodiments may include more or fewer operations than may be described.

The description may use the phrases “in an embodiment,” “in embodiments,” “in some embodiments,” or “in various embodiments,” which may each refer to one or more of the same or different embodiments. Furthermore, the terms “comprising,” “including,” “having,” and the like, as used with respect to embodiments of the present disclosure, are synonymous, and are generally intended as “open” terms (e.g., the term “including” should be interpreted as “including but not limited to,” the term “having” should be interpreted as “having at least,” the term “includes” should be interpreted as “includes but is not limited to,” etc.).

As used herein, “coupled,” along with its derivatives, may mean one or more of the following. “Coupled” may mean a direct physical or electrical coupling or connection, wherein there is no other element coupled or connected between the elements that are said to be coupled with each other. “Coupled” may also mean an indirect physical or electrical coupling or connection, where one or more other elements are coupled or connected between the elements that are said to be coupled with each other.

For the purposes of the present disclosure, the phrase “A/B” means A or B. The phrase “A and/or B” means “(A), (B), or (A and B).” The phrase “at least one of A, B, and C” means “(A), (B), (C), (A and B), (A and C), (B and C), or (A, B and C).” The phrase “(A)B” means “(B) or (AB),” that is, A is an optional element. In addition, although embodiments of the present disclosure may be shown and described as including a particular number of components or elements, embodiments of the disclosure are not limited to any particular number of components or elements.

Turning now to FIG. 1, illustrated is an overview of a cellular phone with autonomous service in accordance with various embodiments. For the embodiments and as shown, cellular phone 100, incorporated with the teachings of the present disclosure, may be coupled with a network 102, e.g., the Internet. Cellular phone 100 may be designed to provide autonomous service to increase the amount of functions performed for user 104. Autonomous services refer to services provided by cellular phone 100 for user 104, without interaction with or intervention by user 104. Although in minority or exception situations, user interaction or intervention may be requested. As will be described in more detail below, in various embodiments, autonomous services are performed based at least in part on dynamically determined service contexts.

For the embodiments, cellular phone 100 may include a number of data collection modules 112. In various embodiments, data collection modules 112 may be configured to collect and store data about user 104, internal operating conditions of cellular phone 100, and/or external environment of cellular phone 100. In various embodiments, data collection modules 112 may collect the data locally (e.g.,

US 9,986,435 B2

3

through local monitoring and/or sensing), as well as from the Internet, thereby significantly broadening the repertoire of data available to support the variety of autonomous services provided as well as enhancing the precision of the autonomous services provided.

Cellular phone **100**, as illustrated, may further include a number of agents **114** configured to perform a number of services for user **104** autonomously, in particular, services for servicing various calls or messages received. Calls may be transmitted to cellular phone **100** via any one of a number of wireless communication protocols, including but not limited to Code Division Multiple Access (CDMA), Global System for Mobile Communication (GSM) and so forth. Messages may be conventional text, email, short messaging service (SMS) or multi-media messaging service (MMS) messages. A message may include a request, e.g., a request to authorize a transaction or approval an action. A message may also report a status of a device or an occurrence of an event.

For some example embodiments, each of agents **114** may be configured to determine, on receipt of a call or a message to be autonomously serviced, a service context, based at least in part on some of the data collected and stored about the user, the internal conditions and the external environment. Examples of a service context may include but are not limited to the user **104** being at home, the user **104** being work, the user **104** being busy, the user **104** being available, battery being low, signal being weak, processor being busy, storage being full, external temperature being cold, humidity being high, and so forth. Further, each of agents **114** may be configured to autonomously service the received call or message, without interaction with the user **104** or substantially without interactions with the user **104**, based at least in part on the determined service context.

FIG. 2 is a block diagram of cellular phone **100** of FIG. 1 in further detail, in accordance with various embodiments. As shown, the example architecture of the cellular phone **100** may include one or more of a user interface **206**, an application layer **208**, data collection and provision modules **222-226**, a services layer **210**, and a network stack **212**. The various interfaces, layers and modules may be implemented by executable instructions stored in various storage media **202**, or executed by one or more processors **201**. Storage medium **202** may be of various types, including but not limited to, e.g., non-volatile memory, such as flash memory. Processor **201** may be of various types also, including but not limited to, e.g., reduced instruction set computer (RISC) processors.

User interface **206** may be configured to support one or more user input and/or output devices through which a user may input commands and data or observe output information. Such devices may include a display device, a speaker, a microphone, a keyboard, a pointing device (e.g., a mouse, a trackball, or a touch pad), or the like.

Cellular phone **100** may be coupled to the network **102** using the network stack **212**. The network stack **212** may be primarily concerned with networking details for coupling the cellular phone **100** to a wireless network. The network stack **212** may be configured to couple the cellular phone **100** to a wireless wide area network (WWAN) or a wireless local area network (WLAN) that may provide access to a broadband network such as the Internet.

The application layer **208** may include agent applications **214** as well as various traditional applications **216** such as, telephone application, text messaging application, or e-mail application. The agent applications (or simply agents) **214** may be configured to service a received call or message on

4

behalf of the user, autonomously, without interaction with the user, or substantially without interaction with the user.

The agents **214** may be designed to determine the service context, on receipt of a call or message to be autonomously serviced. As described earlier, each agent **214** may be configured to determine the service context, on receipt of a call or message to be serviced, based at least in part on some of the data **222** collected about a user, internal operating conditions (system status) **224**, and external environment **226**. Further, each agent application **214** may be configured to thereafter autonomously service the received call or message, based at least in part on the determined service context.

As described earlier, cellular phone **100** may employ a number of data collection modules **112** to collect and store the data **222** about the user, the internal operating conditions (also may be referred to as “system status”) **224**, and the external environment (also may be referred to as “External Data”) **226**, and the collection may be locally and from the Internet. In various embodiments, cellular phone **100** may be provided with one or more sensors **203** in assisting in the local collection of data **222** about the user (User Data), internal operating conditions **224** (System Status), and/or external environment **226** (External Data).

In some embodiments, collecting and storing data **222** about the user may include one or more of collecting and storing data about the user’s current context, e.g., whether the user is at home, at work, or neither, the user’s current status, e.g., whether the user is busy or available, the user’s calendar, the user’s contacts, the user’s to-dos, and so forth. Collecting and storing data about internal operating conditions may include collecting and storing data about one or more of the cellular phone’s power, memory availability, storage availability, CPU utilization, and so forth. Collecting and storing data about the external environment may comprise collecting and storing data about one or more of the cellular phone’s current geographical location, signal strength, signal interference, external temperature, external humidity, and so forth.

For some embodiments, cellular phone **100** may further include a common service layer **210** (Services) located in between the network stack **212** and the application layer **208**. The services layer **210** may be configured to be a gateway between the network and applications operating on cellular phone **100**, including agents **214** configured to autonomously perform services for the user. The services layer **210** may also be configured to route a received call or message to one of the applications **214-216** in application layer **208** to process or service. In various embodiments, service layer **210** may also be designed to perform additional services including, for example, voicemail recording, smart filtering of unwanted communication, or the like.

In various embodiments, agents **214** may be programmed with decision logic (or decision logic trees) of varying levels of complexity. For example, a decision logic may be to simply ignore, forward, or route all calls to voicemail when the user is at work. The decision logic may be refined such that all calls are ignored, forwarded, or routed to voicemail when the user is at work except if those calls are from a certain person or if the user is at her desk versus in a meeting. The decision logic may be broadly categorized into “contexts” (e.g., work, home, vacation, etc.), which may be triggered in certain conditions.

In various embodiments, the agents **214** may be explicitly and/or implicitly programmed to autonomously service a call or a message. Explicit programming may entail explicitly specifying the desired behaviors and the conditions for

US 9,986,435 B2

5

triggering the desired behaviors. To that end, the cellular phone **100** may be endowed with a graphical user interface (GUI) or the like to facilitate the programming interaction. In various embodiments, another computing apparatus may be explicitly programmed with the desired behaviors and then the cellular phone **100** may be synchronized with the other computing apparatus.

Additionally or alternatively, agents **214** may be implicitly programmed to provide the autonomous services. Implicit programming may involve passive learning by the agents **214** in which a user's behavior is observed by the agents **214** and/or by explicit hints provided by the user. An example of passive learning could be a situation in which the agents **214** has an alarm function and it is observed that the user only uses the alarm on weekdays and turns off the alarm function on weekends. In this example, agents **214** may learn to turn the alarm function off on weekends on its own, without requiring the user to explicitly set the conditions. In some embodiments, behavior may be adapted in some embodiments only after a degree of certainty has been achieved (e.g., more than one or two actions may be required before it is considered a "behavior").

In various embodiments, agents **214** may be configured to record the autonomous services provided into a log, and the log may be periodically submitted to an external analysis service for analysis and to provide feedback to the agents. In turn, agents may self-modify their processes in determining the current service context or self-modify the manner in which a call or message is autonomously serviced based at least in part on a determined service context. In various embodiments, agents **214** may be configured to self-modify current service context determination and/or autonomous service based on a determined service context periodically.

FIG. 3 illustrates various examples of autonomous servicing of a call of various embodiments. As illustrated, cellular phone **100** may receive a call **330** through the wireless communication network **102** from another phone **328**, which may be another cellular phone. On receipt of the call **330**, if not filtered, e.g., because it is not a marketing call, service layer **210** may route the call **330** to one of the agents **214** (as opposed to the traditional telephone application **216**). On receipt of the call **330**, the agent **214** may determine the service context at the time, based at least in part on some of the data collected and stored about the user, the internal operating conditions and/or the external environment. Thereafter, the agent **214** may autonomously service the call **330** e.g., by letting the call **330** ring through, routing the call **330** to the traditional telephone application **216**, routing the call **330** to a voice message service (not shown), and so forth.

In various embodiments, cellular phone **100** may receive multiple calls **330** from multiple other phones **328** at the same time. For these embodiments, upon having routed the calls **330** by common service layer **210**, agent **214** may determine the service context by determining the callers, the relative priority of the callers, based at least in part on some of the data collected and stored about the user, the internal operating conditions and/or external environment. Thereafter, agent **214** may route or otherwise dispose the various calls **330** based at least in part on the determined service context. For example, when one of the callers is determined to be the boss of the user, and having priority over all other calls, the boss' call may be allowed to automatically cut in, replacing a lower priority current call, which may be put on hold.

FIG. 4 illustrates various examples of autonomous servicing of messages of various embodiments. As illustrated,

6

cellular phone **100** may receive a message **432** from a remote computing apparatus **430a**, an appliance **430b**, or a device **430c** of another type. The remote computing apparatus **430a** may comprise a mobile electronic device such as, but not limited to, a mobile phone, a laptop computer, or a personal digital assistant, or a substantially stationary computing apparatus, such as a server, a desktop computer or the like. In various embodiments, the remote appliance **430b** may comprise a home appliance, an entertainment or gaming system, or an audio system. In various embodiments, the home appliance **430b** may comprise, but not limited to, a range/oven, a dishwasher, a washer, a dryer, heating/ventilation/cooling system, or the like. In various embodiments, device **430c** may comprise a medical device, a storage device and so forth.

As described earlier, the message **432**, sent from one of the remote computing apparatus **430a**, appliance **430b** or device **430c** of another type (hereinafter, may be referred to collectively as "remote apparatus") may be a conventional communication message, or a message reporting the status of a device or occurrence of an event. The device may be the message sending apparatus itself. Similarly, upon having been routed the message **432** by common service layer **210**, agent **214** may determine the service context, based at least in part on some of the data collected and stored about the user, the internal operating conditions and/or external environment. Thereafter, agent **214** may autonomously service the message **432**, based at least in part on the determined service context.

The interaction with the remote apparatus may include, but is not limited to, an agent **214** monitoring, controlling, obtaining information from, managing data, or otherwise interacting (e.g., receiving and/or transmitting data) with the remote apparatus. In some embodiments, the remote apparatus may be monitored and data may be collected regarding the monitoring and/or the user **104** of cellular phone **100** may be alerted or interrupted in some manner conditioned on the occurrence of an event on the user's cellular phone **100**. The alerts **436** may be conveyed visually, e.g., through blinking lights, audibly, e.g., through audio beeps or other means. In various embodiments, controlling of the remote apparatus may be conditioned on the occurrence of an event on the user's cellular phone **100**.

In some embodiments, for example, the remote appliance **430b** may comprise a home appliance or an entertainment system, alarm, while the other device **430c** may comprise a medical device, which may be monitored and/or controlled by the user's cellular phone **100**. For example, the user's cellular phone **100** may autonomously monitor a medical device **430c** (e.g., a pacemaker, a glucose monitor, etc.). The user's cellular phone **100** may be further configured to send a message **434** to control the medical device **430c** to perform some action in response to some condition (e.g., alert the user **104** if heartbeat or glucose readings are abnormal).

As noted herein, apparatuses, systems, and methods for autonomous service on a cellular phone may be integrated into a work-flow, perhaps in an office-type environment. In some of these embodiments, incoming requests received on the cellular phone **100** (e.g., by email, text, etc.) may be autonomously delegated **452** to another entity or device **450**, sometimes on the basis of recent or long-term activity efforts. The delegation **452** may be addressed in a way, due to heuristic rules or statistical models, to facilitate work objectives. This may allow the user **104** to save time in explicitly reading the request and then delegating it out. This may also allow work to be performed more quickly in that

US 9,986,435 B2

7

the work may be immediately delegated instead of being contingent on some intervention by the user **104**.

In an example, the cellular phone **100** may be part of an infrastructure in which information may be exchanged between various appliances **430b** and cellular phone **100**, which may allow coordination between the appliances **430b** and cellular phone **100**. For example, a message **434** including a command may be issued by the cellular phone **100** to instruct an audio system **430b** within the infrastructure to reduce in volume or mute in response to an incoming call to the cellular phone **100**.

Autonomous service on cellular phone **100** may be used for various social networking applications. In particular, the user's cellular phone **100** may be configured to determine the status of the remote computing apparatus **430a** and take some action for facilitating social networking between the user's cellular phone **100** and the remote computing apparatus **430a** (presumably a "friendly" computing apparatus). In some embodiments, the user's cellular phone **100** may be configured to detect a stimulus including a request from the remote computing apparatus **430a** and take some action for facilitating social networking between the user's cellular phone **100** and the remote computing apparatus **430a** (e.g., providing a message **434** having information regarding the location or status or the user **104**).

In various embodiments, the user's cellular phone **100** may determine whether the remote device **430c** is located nearby, and if so, may alert the user **104**. In some embodiments, the user's cellular phone **100** may determine a calendar schedule of the user of the remote device **430c** and store data regarding the calendar schedule on the user's cellular phone **100**. In still further embodiments, the user's cellular phone **100** may alert (e.g., by text messaging **434**) the user of the remote device **430c** that the user **104** is nearby.

Autonomous service on cellular phone **100** and interaction with the remote apparatus, appliance or device **430a-430c** may be used for management of data stored on the user's cellular phone **100**. Data management may include storing or backing-up of data from the user's cellular phone **100** onto the remote device **430c**. In various ones of these embodiments, for example, the user's cellular phone **100** automatically determines (via one of the agents **214** running in the background on the cellular phone **100**) that the user's cellular phone **100** has data to be backed up or has data for storing onto the remote device **430c**. The user's cellular phone **100** may proceed with the backing up of the data from the cellular phone **100** onto the remote device **430c** by sending messages **434** containing the data to be backed up to remote device **430c**. In some embodiments, the backing up of data may be limited to when the user's cellular phone **100** and the remote device **430c** are within a specified proximity.

In a specific example, a cellular phone **100** with a digital camera interface may be configured via an agent **214** to detect when the cellular phone **100** is within a close proximity of a remote computing apparatus **430a** (e.g., a desktop computer) and automatically backup the stored digital pictures on the desktop computer **430a**. In this specific example, the cellular phone **100** identifies a contextual awareness of the environment (e.g., context="near desktop computer"), and autonomously downloads (or backs up) the digital picture data based on the identified context.

Further examples of tasks that may be performed autonomously may include the handling or smart filtering of incoming emails, calls, or text messages (e.g., by service **210**). Incoming emails or text messages from the remote

8

apparatus, appliance or device **430a-430c** may be automatically forwarded, ignored, or prioritized without any awareness from the user **104**, using agents **214** and/or services **210**.

In various embodiments, the cellular phone **100** may be configured to receive or retrieve data from the remote computing apparatus, **430a-430c** or some other source external to the user's cellular phone **100**, and interrupt the cellular phone **100** or alert **436** the user **104** based at least in part on the content of the data. Whether the user **104** is alerted or the cellular phone **100** is interrupted from its current process(es) may depend at least in part on the occurrence of a condition, indicated by the content of the data. In various embodiments, for example, the cellular phone **100** may be configured to receive or retrieve data on stocks, news, or weather. The cellular phone **100** may autonomously analyze the data, and in embodiments, may also autonomously store the data. If the content of the data meets some condition (e.g., a certain stock price, certain keywords of a news item, certain types of weather, etc.), the cellular phone **100** may then interrupt alert the user **104** or interrupt its current process(es).

In various embodiments, agents **214** of cellular phone **100** may be configured e.g. with one or more agents **214** having security features to reduce the risk of unfriendly reverse engineering or successfully predicting the action of the cellular phone **100**. Accordingly, in various embodiments, the autonomous services performed by an agent **214** with security features may be randomized (within a valid set) such that their prediction may be made more difficult.

Various embodiments described herein may find application for validating or authenticating various activities. For example, credit card or automatic teller machine transactions may be authenticated in accordance with various embodiments. The ignition system of a motor vehicle may similarly require authentication prior to allowing starting up of the motor vehicle. Various electronic devices may be similarly configured to require the provision of authenticating information for access thereto.

In these embodiments, the remote computing apparatus **430a** may comprise an authenticating computing apparatus configured to receive or retrieve over the network **102** a request for an action to occur at a first location (e.g., the motor vehicle's location, the vendor's location, etc.). The authenticating computing apparatus **430a** may be configured to provide a request for authentication information to the user's cellular phone **100**, located at a second location. The authenticating computing apparatus **430a** may be configured to prevent or disallow the requested action to occur until valid authentication information is received from the user's cellular phone **100**.

The user's cellular phone **100**, upon receipt of the authentication request, may provide the requested authentication information to the authenticating computing apparatus **430a**. In various embodiments, the authentication information may be information regarding the location of the user's cellular phone **100** (e.g., coordinates, address, etc.). As noted herein, the location of the user's cellular phone **100** may, by extension, provide information as to the location of the user **104**. As certain requested actions would require the first location (location for the requested action to occur) and the second location (the location of the user's cellular phone **100**/user **104**) to be substantially the same location, providing this location information as the authentication information may be sufficiently authenticating.

For example, if a request is received for a credit card transaction to occur at a store at a particular address, it is

US 9,986,435 B2

9

usually safe to assume that the user **104** would be at the store along with the user's cellular phone **100**. Similarly, if a request is received to start up the user's motor vehicle at a particular location, it is usually safe to assume that the user **104** would be at that motor vehicle along with the user's cellular phone **100**.

The authenticating computing apparatus **430a** may receive or retrieve the authentication information from the user's cellular phone **100** to verify the requested action, and then facilitate the performance of the requested action based at least in part on the authentication information. Facilitation of the requested action may include permitting the requested action to proceed (e.g., if the first location and the second location are substantially the same location). The requested action may, on the other hand, be disallowed if the authentication information is not valid (e.g., the first location and the second location are substantially different locations). In this case, a further action may include alerting the user **104** to notify the user of the requested action and/or requesting the user **104** to take some action to affirmatively authenticate the request action. The further authentication may include, but is not limited to, requesting the user to call the credit card company to provide some indication of approval of the action (e.g., a personal identification number, voice recognition, etc.).

FIG. 5 is a flowchart illustrating a method **500** of autonomous service on a cellular phone, in accordance with various embodiments. A call or message may be received at block **502**. A message may comprise a request, e.g., a request to authorize a transaction, approve an action, and so forth, or a report, reporting e.g., a status of a device, an occurrence of an event, and so forth.

A service context may be determined at block **504**. The service context may be determined based at least in part on some of the data collected and stored, about the user, the internal conditions of the cellular phone, and/or the external environment.

At block **506**, a decision may be made whether to interrupt or alert the user, or to autonomously service the call or message. If it is determined that the user should be interrupted or alerted, the user may be interrupted or alerted accordingly at block **508**. The interruption or alert may be performed in any one of a number of manners, via pop up messages, blinking lights, one or more audio beeps, vibration and so forth. On the other hand, if it is determined that the user should not be interrupted or alerted, the call or message may autonomously be serviced at block **510**, without interaction with the user, based at least in part on the determined current service context.

Computer program products and/or systems may be employed to enable performance of one or more methods as disclosed herein. For example, a computer program product may be adapted to enable a cellular phone to perform autonomous service on behalf of a user.

FIG. 6 is a block diagram of a computer program product **600** with instructions for providing autonomous service on a cellular phone, in accordance with various embodiments. The example computer program product **600** may comprise a computer readable storage medium **632** and a plurality of programming instructions **634** stored in the computer readable medium **632**. In various ones of these embodiments, the programming instructions **634** may be adapted to program a cellular phone to enable the cellular phone to collect data about a user of the cellular phone, internal operating conditions of the cellular phone, and/or external environment of the cellular phone. The collection may be collected locally as well as from the Internet. The instructions **634** may also

10

enable the cellular phone to determine, on receipt of a call or a message, a current service context, based at least in part on some of the data collected and stored. Further, the instructions **634** may also enable the cellular phone to autonomously service the received call or message, without interacting with the user, based at least in part on the determined service context.

Embodiments may have some or all of the instructions depicted in FIG. 6. Embodiments of computer program product **600** may have other instructions in accordance with embodiments described herein. The computer readable medium **632** may take a variety of forms including, but not limited to, volatile and persistent memory, such as, but not limited to, a compact disc (CD), a digital versatile disc (DVD), a solid-state drive, a hard drive, and so forth. Embodiments are not limited to any type or types of computer program products.

Claimed subject matter is not limited in scope to the particular implementations described herein. For example, some implementations may be in hardware, such as employed to operate on a device or combination of devices, for example, whereas other implementations may be in software and/or firmware. Likewise, although claimed subject matter is not limited in scope in this respect, some implementations may include one or more articles, such as a storage medium or storage media. This storage media, such as CD-ROMs, computer disks, flash memory, or the like, for example, may have instructions stored thereon, that, when executed by a system, such as a computer system, computing platform, or other system, for example, may result in execution of a processor in accordance with claimed subject matter, such as one of the implementations previously described, for example. As one possibility, a computing platform may include one or more processing units or processors, one or more input/output devices, such as a display, a keyboard and/or a mouse, and one or more memories, such as static random access memory, dynamic random access memory, flash memory, and/or a hard drive.

There is little distinction left between hardware and software implementations of aspects of systems; the use of hardware or software is generally (but not always, in that in certain contexts the choice between hardware and software can become significant) a design choice representing cost vs. efficiency tradeoffs. There are various vehicles by which processes and/or systems and/or other technologies described herein can be effected (e.g., hardware, software, and/or firmware), and that the preferred vehicle will vary with the context in which the processes and/or systems and/or other technologies are deployed. For example, if an implementer determines that speed and accuracy are paramount, the implementer may opt for a mainly hardware and/or firmware vehicle; if flexibility is paramount, the implementer may opt for a mainly software implementation; or, yet again alternatively, the implementer may opt for some combination of hardware, software, and/or firmware.

In some embodiments, several portions of the subject matter described herein may be implemented via Application Specific Integrated Circuits (ASICs), Field Programmable Gate Arrays (FPGAs), digital signal processors (DSPs), or other integrated formats. However, those skilled in the art will recognize that some aspects of the embodiments disclosed herein, in whole or in part, can be equivalently implemented in integrated circuits, as one or more computer programs running on one or more computers (e.g., as one or more programs running on one or more computer systems), as one or more programs running on one or more processors (e.g., as one or more programs running on one or

US 9,986,435 B2

11

more microprocessors), as firmware, or as virtually any combination thereof, and that designing the circuitry and/or writing the code for the software and/or firmware would be well within the skill of one of skill in the art in light of this disclosure. In addition, those skilled in the art will appreciate that the mechanisms of the subject matter described herein are capable of being distributed as a program product in a variety of forms, and that an illustrative embodiment of the subject matter described herein applies regardless of the particular type of signal bearing medium used to actually carry out the distribution. Examples of a signal bearing medium include, but are not limited to, the following: a recordable type medium such as a floppy disk, a hard disk drive, a Compact Disc (CD), a Digital Versatile Disc (DVD), a digital tape, a computer memory, etc.; and a transmission type medium such as a digital and/or an analog communication medium (e.g., a fiber optic cable, a waveguide, a wired communications link, a wireless communication link, etc.).

With respect to the use of substantially any plural and/or singular terms herein, those having skill in the art can translate from the plural to the singular and/or from the singular to the plural as is appropriate to the context and/or application. The various singular/plural permutations may be expressly set forth herein for sake of clarity.

Although the present disclosure has been described in terms of the above-illustrated embodiments, it will be appreciated by those of ordinary skill in the art that a wide variety of alternate and/or equivalent implementations calculated to achieve the same purposes may be substituted for the embodiments shown and described without departing from the scope of the present disclosure. Those with skill in the art will readily appreciate that embodiments in accordance with the present disclosure may be implemented in a very wide variety of embodiments. This description is intended to be regarded as illustrative instead of restrictive.

What is claimed:

1. A method to perform an action, comprising: receiving, by a first device located at a first geographical location, one or more messages that: indicate geographical location information of a second device located at a second geographical location, and include a request for a first action to be performed by the first device, wherein the one or more messages are received from the second device, and wherein the geographical location information of the second device acts as authentication to allow the first action to be performed by the first device; and autonomously performing, based at least on the received one or more messages, by the first device, the authenticated first action.
2. The method of claim 1, wherein the autonomously performing the authenticated first action includes performing a financial transaction.
3. The method of claim 1, wherein the geographical location information of the second device indicates that the first geographical location and the second geographical location are substantially a same geographical location.
4. The method of claim 3, wherein the geographical location information of the second device indicates that the first device and the second device are at a particular address.
5. The method of claim 3, wherein the geographical location information of the second device indicates that the first device and the second device are at particular coordinates.
6. The method of claim 1, wherein the autonomously performing the authenticated first action includes:

12

autonomously performing a download of data, authenticated in accordance with the geographical location information.

7. The method of claim 1, further comprising:

sending an alert or a message by the first device to the second device.

8. A method to perform an action, comprising:

receiving, by a first device located at a first geographical location, geographical location information of a second device located at a second geographical location and a request for a first action to be performed, wherein the geographical location information of the second device acts as authentication to allow the first action to be performed; and

performing, based on the request, by the first device, the authenticated first action, by performing an autonomous download of data or an autonomous backup of data, authenticated in accordance with the geographical location information of the second device.

9. The method of claim 8, wherein the geographical location information of the second device indicates that the first geographical location and the second geographical location are substantially a same geographical location.

10. The method of claim 9, wherein the geographical location information of the second device indicates that the first device and the second device are at a particular address.

11. The method of claim 9, wherein the geographical location information of the second device indicates that the first device and the second device are at particular coordinates.

12. The method of claim 8, further comprising:

sending an alert or a message by the first device to the second device.

13. The method of claim 8, wherein the autonomously performing the authenticated first action further includes: facilitating social networking between the second device and a remote device.

14. A system to perform an action, comprising:

a first computing apparatus, at a first geographical location, including a processor and a receiving unit, wherein the first computing apparatus is configured to: receive, by the receiving unit, one or more messages that:

indicate geographical location information of a second computing apparatus located at a second geographical location, and

include a request for a first action to be performed, wherein the geographical location information of the second computing apparatus acts as an authentication to allow the first action to be performed; and

perform, based at least on the received one or more messages, by the processor, the authenticated first action,

wherein the performance of the authenticated first action includes autonomous download of data or autonomous backup of data, authenticated in accordance with the geographical location information of the second computing apparatus.

15. The system of claim 14, wherein the geographical location information of the second computing apparatus indicates that the first geographical location and the second geographical location are substantially a same geographical location.

16. The system of claim 15, wherein the geographical location information of the second computing apparatus

US 9,986,435 B2

13

indicates that the first computing apparatus and the second computing apparatus are at a particular address.

17. The system of claim 15, wherein the geographical location information of the second computing apparatus indicates that the first computing apparatus and the second computing apparatus are at particular coordinates. 5

18. The system of claim 14, wherein the first computing apparatus is further configured to:

send an alert or a message to the second computing apparatus. 10

19. The system of claim 14, wherein the performance of the authenticated first action further includes:

facilitate social networking between the second computing apparatus and a remote device.

20. A method to autonomously service a received call or message, the message comprising: 15

collecting and storing data about a user of a mobile device, wherein the data includes data about internal operating condition of the mobile device and data about external environment of the mobile device; 20

receiving, by the mobile device, a call or a message; determining, by the mobile device, previously stored context information about a user of the mobile device, wherein the stored service context information includes data about the internal operating condition of the mobile device and data about the external environment of the mobile device; 25

determining, by the mobile device, a service context in which to perform a first service based on a condition related to the user's previously stored context information; and 30

autonomously performing, by the mobile device, the first service, in response to receiving the call or message based on the service context and the condition being satisfied.

14

21. A method to perform an action, comprising:

receiving, by a first device located at a first location, one or more messages that:

indicate location information of a second device located at a second location, and

include a request for a first action to be performed by the first device, wherein the request is related to the location information of the second device, wherein the one or more messages are received from the second device, and wherein the location information of the second device acts as authentication to allow the first action to be performed by the first device; and

performing, based at least on the received one or more messages, by the first device, the authenticated first action that is related to controlling a third device.

22. The method of claim 21, wherein the second device includes a mobile device.

23. The method of claim 21, wherein the one or more messages include a report of an event occurrence. 20

24. The method of claim 20, further comprising: autonomously performing, by the mobile device, a second service in response to receiving the call or message based on the condition being not satisfied.

25. The method of claim 20, wherein the call or message includes a status report.

26. The method of claim 20, wherein the call or message includes a report of an event occurrence.

27. The method of claim 1, wherein the second device includes a mobile device.

28. The method of claim 21, wherein the first device includes a mobile device.

29. The method of claim 14, wherein the second computing apparatus includes a mobile device.

* * * * *